

ARCHITECTURAL

• *Final color selection should be made from actual color chips.*

- For the most current information available, visit our website at www.mbc.com.
- All products available in smooth or embossed finish.
- Trim available in all colors.
- A 40-year limited paint warranty is available upon written request for all colors except for Brite Red, Copper Metallic, Silver Metallic and Polar White. Please review our sample warranty for complete performance attributes and terms and conditions.

SIGNATURE® 200 STANDARD COLORS

Siliconized Polyester
Polar White is a Straight Polyester.

				
BURNISHED SLATE★ SR .28 SRI 29	POLAR WHITE★ SR .58 SRI 69	CHARCOAL GRAY★ SR .28 SRI 30	LIGHT STONE★ SR .50 SRI 58	RUSTIC RED★ SR .36 SRI 40
				
KOKO BROWN★ SR .28 SRI 30	FERN GREEN★ SR .28 SRI 29	COAL BLACK★ SR .30 SRI 31	HAWAIIAN BLUE★ SR .32 SRI 35	SOLAR WHITE**★ SR .74 SRI 91

SIGNATURE® 300 STANDARD COLORS

KYNAR 500®, HYLAR 5000®, Low Gloss

				
HARBOR BLUE★ SR .28 SRI 30	COLONIAL RED★ SR .34 SRI 37	MEDIUM BRONZE★ SR .33 SRI 36	PACIFIC BLUE★ SR .29 SRI 31	NATURAL PATINA★ SR .41 SRI 47
				
SNOW WHITE★ SR .65 SRI 79	SLATE GRAY★ SR .37 SRI 41	ALMOND★ SR .63 SRI 76	MIDNIGHT BRONZE★ SR .29 SRI 31	CLASSIC GREEN★ SR .28 SRI 30
				
EVERGLADE★ SR .33 SRI 36	BROWNSTONE★ SR .47 SRI 54	TUNDRA★ SR .46 SRI 53	SPRUCE★ SR .36 SRI 40	HUNTER GREEN★ SR .35 SRI 39
				
BRITE RED★ SR .49 SRI 55	BONE WHITE**★ SR .70 SRI 85			

SIGNATURE® 300 METALLIC

KYNAR 500®, HYLAR 5000®, Low Gloss

	
COPPER METALLIC★ SR .45 SRI 51	SILVER METALLIC★ SR .52 SRI 60

Metallic coatings are directional. Panels and trim must be installed oriented in the same direction to prevent perceived shade variances.



** Minimum quantities and/or extended lead times may be required. Please inquire.

Signature® is a registered trademark of NCI Group, Inc. KYNAR 500® is a registered trademark of Arkema, Inc. HYLAR 5000® is a registered trademark of Solvay Solexis.




* ENERGY STAR® Qualified


DESIGNER® SERIES






SHADOWRIB™





NUWALL®



WALL / LINER PANELS




ARTISAN® SERIES




8" and 10" also available


CLASSIC® SERIES





QWIKLOK™



FLEXLOC®




CRAFTSMAN™ SERIES




STANDING SEAM Vertical Leg


LOKSEAM®




BATTENLOK® HS



SUPERLOK®




CURVED BATTENLOK®




Trapezoidal Leg

ULTRA-DEK®



DOUBLE-LOK®



SOLAR REFLECTIVITY (SR)?

Solar reflectivity or reflectance (SR) is the ability of a material to reflect solar energy from its surface back into the atmosphere. The SR value is a number from 0 to 1.0. A value of 0 indicates that the material absorbs all solar energy and a value of 1.0 indicates it is all reflected. Energy Star requires SR testing of both new and aged roof products. New products must have an SR value of 0.25 or higher for steep slope (above 2:12) roofing and an SR value of 0.65 or higher for low slope (2:12 or less) roofing. Aged testing takes 3 years to complete, so not all products that meet the initial requirements are qualified. For more information, please go to www.energystar.gov.

SOLAR REFLECTANCE INDEX (SRI)?

The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. Emissivity is a material's ability to release absorbed energy. To meet LEED requirements, a roofing material must have an SRI of 29 or higher for steep slope (above 2:12) roofing and an SRI value of 78 or higher for low slope (2:12 or less) roofing. For more information, please go to www.usgbc.org.

SR/SRI CHART

SIGNATURE® 300 - KYNAR 500® /HYLAR 5000®

	SR #	SRI #
HARBOR BLUE	.28	30
COLONIAL RED	.34	37
MEDIUM BRONZE	.33	36
PACIFIC BLUE	.29	31
HUNTER GREEN	.35	39
SNOW WHITE	.65	79
SLATE GRAY	.37	41
ALMOND	.63	76
MIDNIGHT BRONZE	.29	31
CLASSIC GREEN	.28	30
EVERGLADE	.33	36
BROWNSTONE	.47	54
TUNDRA	.46	53
SPRUCE	.36	40
NATURAL PATINA	.41	47
BRITRE RED	.49	55
BONE WHITE	.70	85

SIGNATURE® 300 METALLIC - KYNAR 500® /HYLAR 5000®

	SR #	SRI #
COPPER METALLIC	.45	51
SILVER METALLIC	.52	60

SIGNATURE® 200 - SILICONIZED POLYESTER

	SR #	SRI #
BURNISHED SLATE	.28	29
POLAR WHITE	.58	69
CHARCOAL GRAY	.28	30
LIGHT STONE	.50	58
HAWAIIAN BLUE	.32	35
RUSTIC RED	.36	40
KOKO BROWN	.28	30
FERN GREEN	.28	29
COAL BLACK	.30	31
SOLAR WHITE	.74	91

For complete performance specifications, product limitations and disclaimers, please consult MBCI's Paint and Galvalume Plus® warranties. Upon receipt of payment in full, these warranties are available upon request for all painted or Galvalume Plus®, prime products. Sample copies can be found at www.mbcicom or contact your local MBCI Sales Representative.